



Bimetal Temperature Range Master List - (Other ranges available on application. Y = available)

Code	F Ranges	Div	Q	G	H	3,4,5**	Code	C Ranges	Div	Q	G	H	3,4,5**	Code	Dual Ranges	Q	G	H	3,4,5**
F03	-100/100F	2		Y	Y	Y	C03	-70/70C					Y	D03	-100/100F & -70/40C	Y	Y	Y	
F07	-80/120F	2			Y	Y	C07	-50/50C	1		Y	Y	Y	D11	-50/210F & -50/100C				Y
F11	-70/150F	2				Y	C11	-50/100C	2		Y	Y	Y	D23	-40/160F & -40/70C	Y	Y	Y	
F21	-40/120F	2				Y	C23	-40/70C	1	Y	Y	Y	Y						
F23	-40/160F	2	Y	Y	Y	Y		-50/200C	2				Y						
F19	-50/300F	2		Y	Y	Y	C19	-40/160C	2				Y						
F31	-20/120F	2		Y		Y	C31	-20/40C*	1				Y						
F35	0/100F*	1				Y								D55	25/125F & -5/50C*	Y	Y	Y	
F55	25/125F*	1	Y	Y	Y	Y	C55	0/50C*	1/2	Y	Y	Y	Y	D37	0/140F & -15/60C	Y	Y		
F37	0/140F	2				Y	C37	0/60C*					Y	D39	0/150F & -20/70C				Y
F39	0/150F	1			Y	Y	C43	0/100C	1	Y	Y	Y	Y	D43	0/200F & -10/90C	Y	Y	Y	Y
F43	0/200F	2	Y	Y	Y	Y													
F45	0/220F	2		Y	Y	Y	C47	-20/120C	2		Y	Y	Y	D47	0/250F & -20/120C	Y	Y	Y	
F47	0/250F	2	Y	Y	Y	Y	C53	-10/110C	1	Y	Y	Y	Y	D53	20/240F & -10/115C	Y	Y	Y	
F53	20/240F	2	Y	Y	Y	Y	C63	0/150C	1	Y	Y	Y	Y	D63	50/300F & 10/150C	Y	Y	Y	
F63	50/300F	2	Y	Y	Y	Y	C65	0/200C	2	Y	Y	Y	Y	D65	50/400F & 10/200C				Y
F65	50/400F	5				Y	C67	0/250C	2				Y	D67	50/500F & 10/260C	Y	Y	Y	Y
F67	50/500F	5	Y	Y	Y	Y	C69	0/300C	2	Y	Y	Y	Y	D69	50/550F & 10/290C				Y
F69	50/550F	5			Y	Y	C79	0/400C	5		Y	Y	Y						
F79	100/800F	10		Y	Y	Y	C81	50/400C	5	Y	Y	Y	Y	D81	150/750F & 70/400C				Y
F81	150/750F	10	Y	Y	Y	Y	C85	100/500C	5	Y	Y	Y	Y	D85	200/1000F & 100/500C	Y	Y	Y	Y
F85	200/1000F	10	Y	Y	Y	Y													

* = Minimum stem 4"

** Includes all 3", 4", and 5" models (back, bottom, or all-angle)

Bimetal Thermometers Accessories



Accessories

- AS-86** Adapter Kit: permits installation of bimetal thermometer in existing mercury-in glass-industrial thermometer thermowell.
- HT** Heat Transfer Compound (2 oz, 1 lb containers)
- D3** Duct Flange (1/2" NPT)
- CH** T-27 spring handle
- CP** Pan Clip

Calibration

- CC** Certificate of Conformance
- C1** 1 Point Calibration Certificate
- C3** 3 Point Calibration Certificate

Options

Code	Description	Model
MM	Minimum or Maximum resettable pointer (one hand)	3", 5"
MA	Minimum and Maximum resettable pointer (two hands)	3", 5"
TG	Tempered Glass Lens	3", 4", 5"
PC	Plastic Lens	All
SF	Silicone Filled	3", 4", 5"
SD	Silicone Filled, food grade	3", 4", 5"
GF	Glycerine Filled	3", 4", 5"
PS	Pointed Stem	All
3H	316SS Head and Bezel	3", 4", 5"
SS	316SS Stem	All
F5	5/16" diameter stem	3", 4", 5"
S3	3/8" diameter stem	3", 4", 5"
F3	3/8" diameter aluminum sleeve	3", 4", 5"
TF	Teflon Coating (stem only)	All
MB	External Mounting Brackets	G, H
TS	Stainless Steel Tags	All
TP	Paper Tags	All
NL	No Logo Dial	All
BQ	BBQ Dial	3"

Also available on request – Custom dials, special ranges, special configurations.